

## MAINTENANCE SCHEDULE

Perform the Pre-ride Inspection at each scheduled maintenance period.

I : INSPECT AND CLEAN, ADJUST, LUBRICATE OR REPLACE IF NECESSARY

C : CLEAN R : REPLACE A : ADJUST L : LUBRICATE

ITEM		FREQUENCY	WHICHEVER COMES FIRST ↓ →	ODOMETER READING [NOTE (3)]							PAGE
				EVERY	1,000 km (600 mi)	6,400 km (4,000 mi)	12,800 km (8,000 mi)	19,200 km (12,000 mi)	25,600 km (16,000 mi)	32,000 km (20,000 mi)	
*	FUEL LINES			I	I	I	I	I	I		
*	FUEL STRAINER		C	C	C	C	C	C	C		
*	THROTTLE OPERATION		I	I	I	I	I	I	I	134	
*	CARBURETOR-CHOKE			I	I	I	I	I	I		
	AIR CLEANER	NOTE (1)			R		R		R	132	
	CRANKCASE BREATHER	NOTE (2)		C	C	C	C	C	C	140	
	SPARK PLUGS			I	R	I	R	I	R	128	
	ENGINE OIL	YEAR	R	R	R	R	R	R	R	118	
	ENGINE OIL FILTER	YEAR	R	R	R	R	R	R	R	118	
*	CARBURETOR- SYNCHRONIZATION		I	I	I	I	I	I	I		
*	CARBURETOR-IDLE SPEED		I	I	I	I	I	I	I	136	