

# SPECIFICATIONS

---

## ENGINE

Bore and stroke	73 × 64.8 mm (2.87 × 2.55 in)
Compression ratio	10 : 1
Displacement	1,085 cc (66.1 cu-in)
Spark plug	
Standard	CR8EH-9 (NGK) or U24FER-9 (NIPPONDENSO)
For extended high speed riding	CR9EH-9 (NGK) or U27FER-9 (NIPPONDENSO)
Spark plug gap	0.8 – 0.9 mm (0.031 – 0.035 in)
Idle speed	1,000 ± 100 min <sup>-1</sup> (rpm) ... Except SW 1,200 ± 50 min <sup>-1</sup> (rpm) ... SW only

## CHASSIS AND SUSPENSION

Caster	27°30'
Trail	101 mm (4.0 in)
Tire size, front	110/80 V18 (DUNLOP, BRIDGESTONE) 110/80 V18 – V240 (METZELER)
Model equipped with CBS/ABS/TCS	120/70 ZR18 (DUNLOP, BRIDGESTONE)
Tire size, rear	160/70 V17 (DUNLOP, BRIDGESTONE) 160/70 VB17 – V240 (METZELER)
Model equipped with CBS/ABS/TCS	160/70 ZR17 (DUNLOP, BRIDGESTONE)