

MAINTENANCE

MAINTENANCE SCHEDULE

- The U.S. Environmental Protection Agency requires manufacturers to certify that vehicles built after January 1, 1983 comply with applicable noise emission standards for one year or 3,000 km (1,865 miles) after the time of sale to the ultimate purchaser, when operated and maintained according to the instructions provided. Compliance with the terms of the Distributor's Warranty for the Vehicle Noise Emission Control System is necessary in order to keep the noise emission control system in effect. (USA only)
- Perform the Pre-ride Inspection (Page 27) at each scheduled maintenance period.

I: Inspect and Clean, Adjust, Lubricate or Replace, if necessary. C: Clean R: Replace A: Adjust			INITIAL SERVICE PERIOD (First week of operation)	REGULAR SERVICE PERIOD (Every 30 operating days)	Refer to page
*	FUEL LINE	YEAR I			49
*	FUEL STRAINER SCREEN	YEAR C			49
*	THROTTLE OPERATION		I	I	63
*	CARBURETOR CHOKE			I	-
	AIR CLEANER	NOTE 1		C	54
	AIR CLEANER CASE DRAIN TUBE	NOTE 2		I	59
	SPARK PLUG			I	53
*	VALVE CLEARANCE		I	I	55-56
	ENGINE OIL		R	R	46
**	ENGINE OIL STRAINER SCREEN	NOTE 3			47
**	ENGINE OIL CENTRIFUGE FILTER	NOTE 3			48
*	CARBURETOR IDLE SPEED		I	I	50

* SHOULD BE SERVICED BY AN AUTHORIZED HONDA DEALER, UNLESS THE OWNER HAS PROPER TOOLS, SERVICE DATA AND IS MECHANICALLY QUALIFIED. REFER TO THE OFFICIAL HONDA MANUAL.

** IN THE INTEREST OF SAFETY, WE RECOMMEND THESE ITEMS BE SERVICED ONLY BY AN AUTHORIZED HONDA DEALER.