## .mununununununun SPECIFICATIONS.mununununununununun

| DIMENSIONS            |                       |
|-----------------------|-----------------------|
| Overall length        | 1,660 mm (65.4 in)    |
| Overall width         | 1,000 mm (39.4 in)    |
| Overall height        | 1,015 mm (40.0 in)    |
| Wheelbase             | 1,064 mm (41.9 in)    |
| WEIGHT                |                       |
| Dry weight            | 160 kg (478 lbs)      |
| CAPACITIES            |                       |
| Engine oil            | 1.9 l (2.0 US qt)     |
| Fuel tank             | 8.5 g (2.21 US gal)   |
| Fuel reserve capacity | 2.0 l (0.52 US gal)   |
| Passenger capacity    | Operator only         |
| ENGINE                |                       |
| Bore and stroke       | 65 x 60 mm            |
|                       | (2.56 x 2.36 in)      |
| Compression ratio     | 9.0:1                 |
| Displacement          | 199.1 cc (12.1 cu-in) |
| Spark plug gap        | 0.6-0.7 mm            |
|                       | (0.0240.028 in)       |
| Valve clearance       | 0.08 mm               |
|                       | (0.003 in)            |

| CHASSIS AND SUSPENSION  |  |
|---|--|
| Caster angle<br>Trail length<br>Tire size, front<br>rear          | 4°28′<br>18mm (0.71 in)<br>20 x 7.00–8<br>22 x 11.00–8             |
| POWER TRANSMISSION  |  |
| Primary reduction Final reduction Gear ratio, 1st 2nd 3rd 4th 5th | 3.0870<br>3.5000<br>3.5455<br>2.2667<br>1.6316<br>1.2727<br>1.0417 |