

MAINTENANCE SCHEDULE

Perform the Pre-ride Inspection at each scheduled maintenance period.

I : INSPECT AND CLEAN, ADJUST, LUBRICATE OR REPLACE IF NECESSARY

C: CLEAN R: REPLACE A: ADJUST L: LUBRICATE

ITEM		FREQUENCY	WHICHEVER COMES FIRST ↓ EVERY	ODOMETER READING [NOTE 2]						REFER TO PAGE
				1,000 km (600 mi)	6,000 km (3,750 mi)	12,000 km (7,500 mi)	18,000 km (11,250 mi)	24,000 km (15,000 mi)	30,000 km (18,750 mi)	
*	FUEL LINE				I		I		I	
*	THROTTLE OPERATION				I		I		I	126
*	CARBURETOR CHOKE				I		I		I	
*	AIR CLEANER	(NOTE 1)				R			R	122
	SPARK PLUG			I	R	I	R	I	R	116
*	VALVE CLEARANCE		I	I	I		I		I	
	ENGINE OIL		R		R		R		R	110
	ENGINE OIL FILTER		R		R		R		R	112
*	CARBURETOR SYNCHRONIZATION		I		I		I		I	
*	CARBURETOR IDLE SPEED		I	I	I	I	I	I	I	128
	RADIATOR COOLANT	2 YEARS *R			I		I		*R	178
*	COOLING SYSTEM				I		I		I	