

Specifications

■ Main Components

Overall length	CB1100CA	87.4 in (2,220 mm)
	CB1100NA	86.6 in (2,200 mm)
Overall width	CB1100CA	32.7 in (830 mm)
	CB1100NA	31.5 in (800 mm)
Overall height	CB1100CA	44.5 in (1,130 mm)
	CB1100NA	43.3 in (1,100 mm)
Wheelbase	CB1100CA	58.7 in (1,490 mm)
	CB1100NA	58.5 in (1,485 mm)
Minimum ground clearance	CB1100CA	5.3 in (135 mm)
	CB1100NA	5.1 in (130 mm)
Caster angle	CB1100CA	27° 00'
	CB1100NA	26° 00'
Trail	CB1100CA	4.5 in (114 mm)
	CB1100NA	3.9 in (99 mm)
Curb weight	CB1100CA	562 lb (255 kg)
	USA	CB1100NA 556 lb (252 kg)
Curb weight	CB1100CA	560 lb (254 kg)
	Canada	CB1100NA 553 lb (251 kg)
Maximum weight capacity *1		351 lb (159 kg)
Passenger capacity		Rider and 1 passenger
Minimum turning radius		8.9 ft (2.7 m)
Displacement		69.5 cu-in (1,140 cm ³)
Bore x stroke		2.89 x 2.65 in (73.5 x 67.2 mm)

Compression ratio	9.5:1	
Fuel	Unleaded gasoline	
	Recommended: 86 RON or higher	
Tank capacity	4.44 US gal (16.8 L)	
Battery	YTZ14S	
	12 V-11.2 Ah (10 HR)	
Gear ratios	1st	3.083
	2nd	1.941
	3rd	1.478
	4th	1.240
	5th	1.074
	6th	0.964
Reduction ratios (primary / final)	1.652 / 2.222	

*1: Including rider, passenger, all luggage, and accessories.