

■ Service Data

Tire size	CB1100CA	Front	110/80R18M/C 58V
		Rear	140/70R18M/C 67V
	CB1100NA	Front	120/70ZR17M/C (58W)
		Rear	180/55ZR17M/C (73W)
Tire type	CB1100CA	Radial, tube	
	CB1100NA	Radial, tubeless	
Recommended Tires	Front	DUNLOP D205F	
	CB1100CA	Rear	DUNLOP D205
Recommended Tires	Front	BRIDGESTONE BATTLAX SPORT TOURING T30F J DUNLOP ROAD SMART III	
	CB1100NA	Rear	BRIDGESTONE BATTLAX SPORT TOURING T30R J DUNLOP ROAD SMART III
Tire air pressure	Front	36 psi (250 kPa, 2.50 kgf/cm ²)	
	Rear	42 psi (290 kPa, 2.90 kgf/cm ²)	
Minimum tread depth	Front	0.06 in (1.5 mm)	
	Rear	0.08 in (2.0 mm)	
Spark plug	(standard)	LMAR8A-9S (NGK)	
Spark plug gap		0.03 - 0.04 in (0.8 - 0.9 mm)	
Idle speed		1,100 ± 100 rpm	

Recommended engine oil	API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, ProHonda GN4 4-stroke oil (USA & Canada) or Honda 4-stroke oil, or an equivalent motorcycle oil		
	After draining	4.0 US qt (3.8 L)	
Engine oil capacity	After draining & engine oil filter change	4.1 US qt (3.9 L)	
	After disassembly	5.2 US qt (4.9 L)	
Recommended brake (clutch) fluid	Honda DOT 4 Brake Fluid		
Recommended drive chain lubricant	Pro Honda HP Chain Lube or equivalent		
Drive chain slack	1.0 - 1.4 in (25 - 35 mm)		
Standard drive chain	DID50VA11 or RK50HFOZ6		
	No. of links	110	
Standard sprocket sizes	Drive sprocket	18T	
	Driven sprocket	40T	