

Specifications

■ Service Data

Tire size	Front	120/70ZR17M/C (58W)
	Rear	180/55ZR17M/C (73W)
Tire type		Radial, tubeless
Recommended Tires	Front	BRIDGESTONE BT015F RADIAL L
	Rear	BRIDGESTONE BT015R RADIAL L
Tire air pressure	Front	36 psi (250 kPa, 2.50 kgf/cm ²)
	Rear	42 psi (290 kPa, 2.90 kgf/cm ²)
Minimum tread depth	Front	0.06 in (1.5 mm)
	Rear	0.08 in (2.0 mm)
Spark plugs	(standard)	IMR9E-9HES (NGK) or VUH27ES (DENSO)
Spark plug gap	(non-adjustable)	0.03 to 0.04 in (0.80 to 0.90 mm)
Idle speed	(non-adjustable)	1,200 ± 100 rpm
Recommended engine oil		API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, Pro Honda GN4 4-stroke oil or Honda 4-stroke oil or an equivalent motorcycle oil

Engine oil capacity	After draining	2.9 US qt (2.7 liters)
	After draining & filter change	3.2 US qt (3.0 liters)
	After disassembly	3.8 US qt (3.6 liters)
Recommended drive chain lubricant	Pro Honda HP Chain Lube or equivalent lubricant	
Drive chain slack	1 to 1 3/8 in (25 to 35 mm)	
Standard drive chain	DID 50VA8	
	No. of links	116
Standard sprocket sizes	Front sprocket 16T	
	Rear wheel sprocket 44T	
Recommended brake (clutch) fluid	Honda DOT 4 Brake Fluid	
Cooling system capacity	3.17 US qt (3.00 liters)	
Recommended coolant	Pro Honda HP Coolant	