

Specifications

■ Service Data

| | | |
|-------------------|----------------------------------|---|
| Tire size | Front | 120/80-12 65J |
| | Rear | 130/80-12 69J |
| Tire type | | Bias-ply, tubeless |
| Recommended Tire | Front | VEE RUBBER V133 |
| | Rear | VEE RUBBER V133 |
| Tire air pressure | Front | 29 psi (200 kPa, 2.00 kgf/cm ²) |
| | Rear | 29 psi (200 kPa, 2.00 kgf/cm ²) |
| Spark plug | (standard) | CPR6EA-9 (NGK) or U20EPR9 (DENSO) |
| | (For extended high speed riding) | CPR7EA-9 (NGK) or U22EPR9 (DENSO) |

| | | |
|-----------------------------------|---|-------------------|
| Spark plug gap | 0.03 - 0.04 in (0.8 - 0.9 mm) | |
| Idle speed | (non-adjustable) | 1,400 ± 100 rpm |
| Recommended engine oil | API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, Pro Honda GN4 4-stroke oil (USA & Canada) or Honda 4-stroke oil, or an equivalent motorcycle oil | |
| | After draining | 1.0 US qt (0.9 L) |
| Engine oil capacity | After disassembly | 1.2 US qt (1.1 L) |
| Recommended brake fluid | Honda DOT 3 or DOT 4 Brake Fluid | |
| Recommended drive chain lubricant | Pro Honda HP Chain Lube or equivalent | |
| Drive chain slack | 1 3/16 - 1 9/16 in (30 - 40 mm) | |
| Standard drive chain | DID 420D2 or RK 420SB2TK | |
| | No. of links | 98 |
| Standard sprocket size | Drive sprocket | 15T |
| | Driven sprocket | 34T |