

LIGHTS/METERS/SWITCHES

SPECIFICATIONS

ITEM		SPECIFICATIONS
Bulbs	Headlight (Hi/Lo)	12V - 60/55W
	Position light (Except U type)	12V - 4W
	Brake/taillight	12V - 21/5W × 2
	Turn signal light	12V - 21W × 4
	Instrument light	12V - 1.7W × 3
	Turn signal indicator	12V - 1.7W × 2
	High beam indicator	12V - 1.7W
	Neutral indicator	12V - 1.7W
Fuse	Oil pressure indicator	12V - 1.7W
	Main fuse	30 A
Fan motor switch	Sub fuse	10 A × 4
	Start to close (ON)	98 - 102 °C (208 - 216 °F)
	Stop to open	93 - 97 °C (199 - 207 °F)
Coolant temperature sensor resistance	at 80 °C/176 °F	45 - 60 Ω
	at 120 °C/248 °F	10 - 20 Ω

TORQUE VALUES

Oil pressure switch	12 N·m (1.2 kgf·m , 9 lbf·ft)	Apply sealant to the threads
Oil pressure switch terminal screw	2 N·m (0.2 kgf·m , 1.4 lbf·ft)	
Neutral switch	12 N·m (1.2 kgf·m , 9 lbf·ft)	
Side stand pivot bolt	15 N·m (1.5 kgf·m , 11 lbf·ft)	
Side stand pivot lock nut	39 N·m (4.0 kgf·m , 29 lbf·ft)	
Side stand switch mounting bolt	10 N·m (1.0 kgf·m , 7 lbf·ft)	ALOC bolt
Ignition switch mounting bolt	25 N·m (2.5 kgf·m , 18 lbf·ft)	Apply a locking agent to the threads
Coolant temperature sensor unit	10 N·m (1.0 kgf·m , 7 lbf·ft)	Apply sealant to the threads