

	Item	English	Metric	
Carburetor	Type	Piston valve		
	Setting mark	7A		
	Main jet	#120		
	Slow jet	# 40		
	Air screw opening	1±3/8 turns		
	Float height	0.866 in.	26 mm	
Drive train	Clutch	Wet multi plate type		
	Transmission	5-speed constant mesh		
	Primary reduction	1.708		
	Gear ratio I	2.500		
	Gear ratio II	1.708		
	Gear ratio III	1.333		
	Gear ratio VI	1.097		
	Gear ratio V	1.939		
	Final reduction	2.667, drive sprocket 18 T, driven sprocket 48 T		
	Gear shift pattern	Left foot operated return system		
Electrical	Ignition	Battery and ignition coil		
	Starting system	Starting motor or kick starter		
	Alternator	Three phase A.C. generator 12 V/0.21 kW/5,000 rpm		
	Battery capacity	12 V-14 AH		
	Spark plug	NGK DBES-L, NDX 24ES		
	Headlight	Low/high	12 V-40 W/50 W	
	Tail/stoplight	Tail/stop	12 V-7/23 W (SEA TRADE No. 1157)	
	Turn signal-light	Front/rear	12 V-23/23 W	
	Speedometer light	12 V-3 W		
	Tachometer light	12 V-3 W		
	Neutral indicator light	12 V-3 W		
	Turn signal indicator light	12 V-3 W		
	High beam indicator light	12 V-3 W		