

2. CARBURETOR

Carburetor Setting Table

Setting number	PD42A
Main jet	No. 105
Slow jet	No. 35
Pilot screw opening	1.3/4
Float height	14.5 mm (0.571 in.)

3. CONNECTING ROD

The connecting rod cap tightening torque is changed from 2.0 kg-m (14.5 lbs-ft) to 2.6 kg-m (18.8 lbs-ft).

4. AIR CLEANER

See page 274.

5. SPECIFICATIONS

Item	
DIMENSION	
Overall length	2,210 mm (87.0 in.)
Overall width	860 mm (33.9 in.)
Overall height	1,185 mm (46.7 in.)
Wheelbase	1,480 mm (58.3 in.)
Seat height	830 mm (32.7 in.)
Foot peg height	325 mm (12.8 in.)
Ground clearance	135 mm (5.3 in.)
Dry weight	232.5 kg (512.6 lb.)
FRAME	
Type	Double cradle
Front suspension, travel	Telescopic fork, travel 141.5 mm (5.6 in.)
Rear suspension, travel	Swing arm, travel 86.3 mm (3.4 in.)
Front tire size, type	3.25H-19-4PR, Rib
air pressure	Up to 90 kg (200 lb.) load: 2.0 kg/cm ² (28 psi)
	Up to vehicle capacity load: 2.25 kg/cm ² (32 psi)
Rear tire size, type	4.00H-18-4PR Block
air pressure	Up to 90 kg (200 lb.) load: 2.0 kg/cm ² (28 psi)
	Up to vehicle capacity load: 2.8 kg/cm ² (40 psi)
Front brake	Disc brake
Rear brake	Disc brake
Fuel capacity	18 lit. (4.8 U.S. gal., 4.0 Imp. gal.)
Fuel reserve capacity	4.5 lit. (1.2 U.S. gal., 1.0 Imp. gal.)
Caster angle	62.5°
Trail length	113.5 mm (4.47 in.)
Front fork oil capacity	145-155 cc (5.3-5.4 ounces.)