

After '93:

Per from the PRE-RIDE INSPECTION in the Owner's Manual at each scheduled maintenance period.

I: Inspect and Clean, Adjust, Lubricate, or Replace if necessary.

R: Replace, L: Lubricate

The following items require some mechanical knowledge. Certain items (particularly those marked * and **) may require more technical information and tools. Consult your authorized Honda dealer.

Item	Frequency	Whichever Comes First ↓ Note	Odometer Reading (Note 1)								Refer to page		
			→	× 1000 mi	0.6	4	8	12	16	20		24	
			× 100 km										10
EMISSION RELATED ITEMS	* Fuel Line					I			I			I	Note 5
	* Throttle Operation					I			I			I	Note 5
	* Carburetor Choke					I			I			I	Note 5
	* Air Cleaner		Note 2						R			R	3-6
	Spark Plug				I	R	I	R	I	R		R	3-7/Note 5
	* Valve Clearance								I				3-7
	Engine Oil			R		R		R		R		R	Note 5
	Engine Oil Filter			R		R		R		R		R	Note 5
	* Carburetor Synchronization					I		I		I		I	3-11/Note 5
	* Carburetor Idle Speed			I	I	I	I	I	I	I	I	I	Note 5
	Radiator Coolant		Note 3				I		I			R	Note 5
	* Cooling System						I		I			I	Note 5
	* Secondary Air Supply System						I		I			I	Note 5
	* Evaporative Emission Control System							I				I	Note 5
NON-EMISSION RELATED ITEMS	Drive Chain		I,L every 600 mi (1,000km)								3-12		
	Brake Fluid		Note 3			I	I	R	I	I	R		Note 5
	Brake Pad Wear					I	I	I	I	I	I		Note 5
	Brake System			I		I		I		I			Note 5
	* Brake Light Switch					I		I		I			Note 5
	* Headlight Aim					I		I		I			3-15
	Clutch System					I		I		I			Note 5
	Clutch Fluid		Note 3		I	I	R	I	I	R			Note 5
	Side Stand					I		I		I			3-15
	* Suspension					I		I		I			Note 5
	* Nuts, Bolts, Fasteners			I		I		I		I			Note 5
** Wheels/Tires					I		I		I			Note 5	
** Steering Head Bearings			I		I		I		I			Note 5	

* Should be serviced by an authorized Honda dealer, unless the owner has proper tools and service data and is mechanically qualified.

** In the interest of safety, we recommend these items be serviced only by an authorized Honda dealer.

Notes: 1. At higher odometer readings, repeat at the frequency interval established here.

2. Service more frequently when riding in unusually wet or dusty areas.

3. Replace every 2 years, or at indicated odometer interval, whichever comes first.

Replacement requires mechanical skill.

4. California type only.

5. Refer to the Common Service Manual.