

MAINTENANCE

ITEM		SPECIFICATIONS	
Engine idle speed	Except SW, AR, IIG type		1,100 ± 100 min ⁻¹ (rpm)
	AR, IIG type		1,200 ± 100 min ⁻¹ (rpm)
	SW type		1,200 ± 50 min ⁻¹ (rpm)
Drive chain slack			30 – 40 mm (1.2 – 1.6 in)
Recommended brake fluid			DOT 4
Recommended clutch fluid			DOT 4 brake fluid
Cold tire pressure	Driver only	Front	250 kPa (2.50 kgf/cm ² , 36 psi)
		Rear	290 kPa (2.90 kgf/cm ² , 42 psi)
	Driver and passenger	Front	250 kPa (2.50 kgf/cm ² , 36 psi)
		Rear	290 kPa (2.90 kgf/cm ² , 42 psi)
Tire size		Front	120/70ZR17 (58W)
		Rear	180/55ZR17 (73W)
Tire brand	DUNLOP	Front	D204FK
		Rear	D204K
	MICHELIN	Front	MACADAM 90X G
		Rear	MACADAM 90X G
Minimum tread depth		Front	1.5 mm (0.06 in)
		Rear	2.0 mm (0.08 in)

TORQUE VALUES

Spark plug	14 N·m (1.4 kgf·m , 10 lbf·ft)	
Crankshaft hole cap	15 N·m (1.5 kgf·m , 11 lbf·ft)	Apply grease to the threads.
Timing hole cap	10 N·m (1.0 kgf·m , 7 lbf·ft)	Apply grease to the threads.
Oil filter cartridge	10 N·m (1.0 kgf·m , 7 lbf·ft)	Apply oil to the threads and O-ring.
Engine oil drain bolt	29 N·m (3.0 kgf·m , 22 lbf·ft)	
Vacuum port socket bolt	3 N·m (0.34 kgf·m , 2.5 lbf·ft)	
Rear axle nut	93 N·m (9.5 kgf·m , 69 lbf·ft)	
Rear reservoir mounting bolt	9 N·m (0.9 kgf·m , 6.5 lbf·ft)	
Clutch reservoir stopper plate screw	1 N·m (0.12 kgf·m , 0.9 lbf·ft)	

TOOL

Oil filter wrench	07HAA-PJ70100
Drive chain tool set	07HMH-MR10103