

**BATTERY/CHARGING SYSTEM SPECIFICATIONS**

ITEM			SPECIFICATIONS
Battery	Type	XL125LK, XR125LK	YTX4L-BS
		XR125LEK	YTX5L-BS
	Capacity	XL125LK, XR125LK	12 V – 3 Ah (10 HR)
		XR125LEK	12 V – 4 Ah (10 HR)
	Current leakage		0.01 mA max.
	Voltage (20°C/68°F)	Fully charged	Above 12.8 V
		Needs charging	Below 12.3 V
	Charging current	XL125LK, XR125LK	Normal
Quick			4.0 A/0.5 h
XR125LEK		Normal	0.5 A/5 – 10 h
		Quick	5.0 A/0.5 h
Alternator	Capacity	0.12 kW/5,000 min <sup>-1</sup> (rpm)	
	Charging coil resistance (20°C/68°F)		0.2 – 1.2 Ω

**LIGHTS/METER/SWITCHES SPECIFICATIONS**

ITEM			SPECIFICATIONS
Bulbs	Headlight (High/Low beam)		12 V – 35/35 W
	Position light		12 V – 4 W
	Brake/taillight		12 V – 21/5 W
	License light (XR125LK/LEK)		12 V – 5 W
	Front turn signal light	XR125LK/LEK	12 V – 16 W x 2
		XL125LK	12 V – 15 W x 2
	Rear turn signal light	XR125LK/LEK	12 V – 16 W x 2
		XL125LK	12 V – 15 W x 2
	Instrument light		12 V – 1.7 W
	Turn signal indicator		12 V – 3.4 W
	High beam indicator		12 V – 3.4 W
	Neutral indicator		12 V – 3.4 W
Fuse	Main fuse		15 A
	Sub fuse		10 A