



SERVICE INFORMATION	2-1
TROUBLESHOOTING	2-1
ENGINE OIL LEVEL CHECK	2-2
ENGINE OIL CHANGE	2-2
ENGINE OIL FILTER SCREEN	2-3
LUBRICATION POINTS	2-4

SERVICE INFORMATION

GENERAL INSTRUCTIONS

- This section describes inspection and replacement of engine oil and cleaning of the oil filter screen.
- Oil pump service is described in Section 8.

SPECIFICATIONS

Oil capacity **2.0 liter (2.1 US qt, 1.8 Imp qt) at engine assembly**
1.7 liter (1.8 US qt, 1.5 Imp qt) at oil change

Oil recommendation Use HONDA 4-STROKE OIL or equivalent.
 API SERVICE CLASSIFICATION: SE
 VISCOSITY:
 SAE 10W-40

Other viscosities shown in the chart may be used when the average temperature in your riding area is within the indicated range.

Oil pump delivery **4.9 lit (5.2 US qt)/min at 5,000 rpm**

TORQUE VALUE

Oil drain bolt 20-30 N·m (2.0-3.0 kg·m, 14-21 ft·lb)

TROUBLESHOOTING

Oil Level Too Low

1. Normal oil consumption
2. External oil leaks
3. Worn piston rings

Oil Contamination

1. Oil not changed often enough
2. Faulty head gasket

OIL VISCOSITIES

