



SERVICE INFORMATION	13-1
TROUBLESHOOTING	13-2
HEADLIGHT	13-3
SPEEDOMETER	13-3
HANDLEBAR	13-4
FRONT WHEEL	13-6
FRONT FORK	13-13
STEERING STEM	13-19

## SERVICE INFORMATION

### GENERAL INSTRUCTION

- A jack or other support is required to support the motorcycle.

### TOOL SPECIAL

6 mm Hex wrench	07917-3230000	Commercially available in U.S.A.
Snapping pliers	07914-3230001	
Ball race remover	07946-4300200	
Ball race driver	07953-MA00000	
Steering stem driver	07946-4300100	
Steering stem socket	07916-3710100	
Fork seal driver	07947-3710101	

### COMMON

Bearing driver outer 32 x 35 mm	07746-0010100	Commercially available in U.S.A.
Bearing driver handle outer A	07749-0010000	
Driver pilot 15 mm	07746-0040300	
Socket wrench 30 x 32 mm	07716-0020400	
Extension bar	07716-0020500	
Bearing driver outer, 42 x 47 mm	07746-0010300	

ITEMS		STANDARD	SERVICE LIMIT
Axle shaft runout		_____	0.2 mm (0.01 in)
Front wheel rim runout	Radial	_____	2.0 mm (0.08 in)
	Axial	_____	2.0 mm (0.08 in)
Brake drum I.D.		130 mm (5.12 in)	131 mm (5.16 in)
Brake shoe thickness		4.0 mm (0.16 in)	2.0 mm (0.1 in)
Front fork spring free length		617.5 mm (24.31 in)	605.1 mm (24 in)
Front fork tube runout		_____	0.2 mm (0.008 in)
Front fork oil level		181 mm (7.1 in)	_____
Front fork air pressure		30 kPa (0.3 kg-m <sup>-2</sup> , 4.3 psi)	_____
Wheel bearing	Radial	_____	0.10 mm (0.004 in)
	Axial	_____	0.05 mm (0.002 in)